



大山電線電纜股份有限公司

Dah San Electric Wire & Cable Corp.

ADDRESS: 369, SEC.3, YUN-LIN RD., TOU-LIU CITY YUN-LIN SHEN, TAIWAN, R.O.C.

TEL: 886-5-5222-333 ext: 123 FAX: 886-5-5224-285 E-MAIL: dah.san@msa.com.tw

WEB: www.dahsan.com.tw

COAXIAL CABLE SPEC.

MIL-C-17/155A

	CONDUCTOR		INSULATION		BRAID			SHEATH	
	Material	Constitute NO./MM	Material	Diameter MM	Material	coverage % (nom.)	Constitute	Material	O.D. MM
RG-58C/U	TINNED COPPER	19 / 0.18	PE	2.95	TINNED COPPER	94.2	16/7/0.13	MNPVC	4.95±0.1

DC resistance (max. at 20°C) : 1.24 ohms per 100 feet.

Spark test : 5,000 V rms.

Voltage withstanding : 5,000 V rms / 1 Minute

Characteristic impedance : 50 ohms ±2 .

Attenuation : dB PER 100FT

4.0 dB@ 50 MHZ ; 6.5 dB@100 MHZ

17.0 dB@400 MHZ ; 28 dB@1 GHZ.

Capacitance : 32.2 PF per foot, maximum.