



**SPECIFICATION**

Current Rating: 5AMP  
 Di electric Strength: 1000V For 1minute  
 Insulator Resistance: 1000MΩ min. at DC500V  
 Temperature: -55°C ~ +105 °C

**MATERIAL**

Insulator: PBT+30 % Glass Fiber (UL 94V-0)  
 Contact: Phosphor Bronze or Brass  
 Contact Plated: Cold Over Nickel  
 Shell: Steel (Zinc Plated or Tin Plated)

|            |                    |              |         |
|------------|--------------------|--------------|---------|
| 序号/Rev.No. | 更改记录/Revision note | 签名/Signature | 日期/Date |
|------------|--------------------|--------------|---------|

|                           |               |               |                |                           |           |
|---------------------------|---------------|---------------|----------------|---------------------------|-----------|
| 设计/Desigined by           | 绘图/Drawing by | 审核/Checked by | 批准/Approved by | 未注公差<br>General Tolerance |           |
|                           |               |               |                | x. ±0.2                   | x. ±2'    |
|                           |               |               |                | .x ±0.1                   | .x' ±1'   |
|                           |               |               |                | .xx ±0.05                 | .x' ±0.5' |
|                           |               |               |                | .xxx ±0.01                | .xx ±0.1' |
|                           |               |               |                | 单位/Units: <b>MM</b>       |           |
| XINYA ELECTRONIC CO., LTD |               | 图名/Title      | 文件编号/File No.  | 页序/Sheet                  |           |
| 新亚电子                      |               | 150A-10360    |                |                           |           |
| 备注/Remark                 |               |               |                |                           |           |