



TOP Electronic Components S.A.

66 ALKMINIS & ARISTOVOULOY St.,

118 53 K. PETRALONA,

ATHENS, GREECE.

Tel : +30-210-3428690

Fax : +30-210-3428692

Email : info@topelcom.gr

VAT. Number : 094356121

HYC-3 Specifications

Characteristics

Impedance: 75+/-3 Ohm

Velocity of Propagation: 85%

Return Loss: >=20dB

Description:

Construction

Center Conductor: 1.02mm Copper Clad Steel (+/-0.2mm)

Dielectric: 4.65mm Foam PE (+/-0.2mm)

Shield: Aluminum Foil

Braid Coverage: 0.12/64 @ 40%-50% Aluminum braid

Jacket: 6.80mm PVC (+/-0.2mm)

Characteristics

Impedance: 75+/-3 Ohm

Velocity of Propagation: 85%

Return Loss: >=20dB

Attenuation[@ 68F. (20.)]

5MHz	2.5dB
55MHz	6.0dB
211MHz	10.6dB
270MHz	11.6dB
300MHz	12.2dB
330MHz	12.9dB
400MHz	14.2dB
450MHz	15.0dB
550MHz	16.8dB
750MHz	19.6dB
870MHz	21.2dB
1000MHz	22.9dB