

## Installation Cables / PVC Insulated, PVC Sheathed Installation Cables

### MULTICORE PVC INSULATED, PVC SHEATHED FLAT CABLES



---

<b>Type</b>	: NYIFY
<b>Standard</b>	: DIN VDE 0250-201
<b>Construction</b>	: 1) Conductor : EN 60228 Class 1-2 2) Insulation : PVC 3) Sheath : PVC
<b>Application</b>	: In dry and damp rooms, locations and store rooms subject to fire and explosions hazards, but not for underground laying. For permanent installations clear from or in and under plaster.
<b>Technical Data</b>	: » Max. Operating Temperature : +70°C » Rated Voltage : 300/500 V

---

RATED CROSS SECTION (mm <sup>2</sup> )	COPPER CONDUCTOR	INSULATION THICKNESS (mm)	SHEATH THICKNESS (mm)	APPROX. OVERALL DIAMETER(mm)	APPROX. NET WEIGHT (kg/km)
2x1	1.12	0.40	0.70	3.50x11.0	51
2x1.5	1.37	0.40	0.80	3.90x11.8	65
2x2.5	1.73	0.50	0.90	4.70x13.4	95
2x4	2.20	0.60	0.90	5.3x14.6	131
2x6	2.70	0.70	1.00	6.2x16.4	184
3x1	1.12	0.40	0.70	3.4x15.2	72
3x1.5	1.37	0.40	0.80	3.9x16.7	97
3x2.5	1.73	0.50	0.90	4.7x19.1	142
3x4	2.20	0.60	0.90	5.3x20.9	196
3x6	2.70	0.70	1.00	6.2x23.6	276