

Table of specifications

MC type Magnetic Contactors



Frame size			22AF			
Type	screws clamp terminals		MC-9b	MC-12b	MC-18b	MC-22b*
Number of poles			3pole			
Rated operational voltage, Ue			690V			
Rated insulation voltage, Ui			690V			
Rated frequency			50/60Hz			
Rated impulse withstand voltage, Uimp			6kV			
Maximum operating rate in operating cycles per hour(AC3)			1800 operations per hour			
Durability	Mechanical		15 mil. operations			
	Electrical		2.5 mil. operations			
Current and power	AC-1, Thermal current	A	25	25	32	40
	AC-3 200/240V	kW	2.5	3.5	4.5	5.5
		A	11	13	18	22
	380/440V	kW	4	5.5	7.5	11
		A	9	12	18	22
	500/550V	kW	4	7.5	7.5	15
		A	7	12	13	20
	690V	kW	4	7.5	7.5	15
		A	6	9	9	18
UL rating (50/60Hz)	Continuous current	A	25	25	40	40
	Single phase	110~120V HP	0.5	0.75	1	2
		220~240V HP	1.5	2	3	3
		200~208V HP	2	3	5	7.5
	Three phase	220~240V HP	3	5	7.5	10
		440~480V HP	5	7.5	10	15
		550~600V HP	7.5	10	15	20
	NEMA size		00	00	0	1
Size and weight	AC control	Weight kg	0.34			
		Size(W×H×D) mm	45×73.5×86			
	DC control	Weight kg	0.51			
		Size(W×H×D) mm	45×73.5×117.7			
Auxiliary(standard)			1a1b			
Auxiliary	Side mount		UA-1			
	Front mount		AU-2, AU-4			

