

Table of specifications

MC type Magnetic Contactors



Frame size		40AF	
Type	screws clamp terminals	MC-32a	MC-40a
Number of poles		3pole	
Rated operational voltage, Ue		690V	
Rated insulation voltage, Ui		1000V	
Rated frequency		50/60Hz	
Rated impulse withstand voltage, Uimp		8kV	
Maximum operating rate in operating cycles per hour(AC3)		1800 operations per hour	
Durability	Mechanical	12 mil. operations	
	Electrical	2 mil. operations	
Current and power	AC-1, Thermal current	A	50 60
	AC-3 200/240V	kW	7.5 11
		A	32 40
	380/440V	kW	15 18.5
		A	32 40
	500/550V	kW	18.5 22
		A	28 32
	690V	kW	18.5 22
		A	20 23
UL rating (50/60Hz)	Continuous current	A	50 60
	Single phase	110~120V HP	2 3
		220~240V HP	5 7.5
		200~208V HP	7.5 15
	Three phase	220~240V HP	10 15
		440~480V HP	20 30
		550~600V HP	25 30
	NEMA size		1 1
	Size and weight	AC control	Weight kg
		DC control	Size(W×H×D) mm
			69×83×93
Auxiliary(standard)	Auxiliary	Side mount	UA-1
		Front mount	AU-2, AU-4

