

# Table of specifications

## MC type Magnetic Contactors



Frame size		65AF		
Type		MC-50a	MC-65a	
screws clamp terminals		●	●	
Number of poles		3pole		
Rated operational voltage, Ue		690V		
Rated insulation voltage, Ui		1000V		
Rated frequency		50/60Hz		
Rated impulse withstand voltage, Uimp		8kV		
Maximum operating rate in operating cycles per hour(AC3)		1800 operations per hour		
Durability	Mechanical	12 mil. operations		
	Electrical	2 mil. operations		
Current and power	AC-1, Thermal current AC-3 200/240V	A kW	70 15	100 18.5
		A	55	65
	380/440V	kW	22	30
		A	50	65
	500/550V	kW	30	33
		A	43	60
	690V	kW	30	33
		A	28	35
UL rating (50/60Hz)	Continuous current Single phase	A HP	70 3	100 5
	220-240V	HP	10	15
	200-208V	HP	20	25
	Three phase	220-240V	HP	25
	440-480V	HP	40	50
	550-600V	HP	50	60
	NEMA size		2	2
Size and weight	AC control DC control	Weight kg Size(W × H × D) mm	1.05 79 × 106 × 122	
		Weight kg	1.3	
		Size(W × H × D) mm	79 × 106 × 149	
Auxiliary (standard)				
Auxiliary	Side mount	UA-1		
	Front mount	AU-2, AU-4		

