

# Table of specifications

## MC type Magnetic Contactors



Frame size			400AF	
Type		screws clamp terminals	MC-330a	MC-400a
Number of poles			3pole	
Rated operational voltage, Ue			690V	
Rated insulation voltage, Ui			1000V	
Rated frequency			50/60Hz	
Rated impulse withstand voltage, Uimp			8kV	
Maximum operating rate in operating cycles per hour(AC3)			1200 operations per hour	
Durability	Mechanical		5 mil. operations	2.5 mil. operations
	Electrical		1 mil. operations	0.5 mil. operations
Current and power	AC-1, Thermal current AC-3	A	350	450
	200/240V	kW	90	125
	A		330	400
	380/440V	kW	160	200
	A		330	400
	500/550V	kW	160	225
	A		280	350
	690V	kW	200	250
	A		225	300
UL rating (50/60Hz)	Continuous current Single phase	A	350	450
	110~120V	HP	-	-
	220~240V	HP	-	-
	200~208V	HP	100	125
	Three phase	220~240V	125	150
	440~480V	HP	250	300
	550~600V	HP	250	300
	NEMA size		5	5
Size and weight	AC control	Weight kg	9.2	
	DC control	Weight kg	163 × 243 × 198	
Auxiliary (standard)			2a2b	
Auxiliary	Side mount		AU-100 (Max.4NO4NC)	
	Front mount		-	

