

Table of specifications

MC type Magnetic Contactors



Frame size		22AF				
Type	screws clamp terminals	MC-12b	MC-18b	MC-22b*		
Number of poles		3pole				
Rated operational voltage, Ue		690V				
Rated insulation voltage, Ui		690V				
Rated frequency		50/60Hz				
Rated impulse withstand voltage, Uimp		6kV				
Maximum operating rate in operating cycles per hour(AC3)		1800 operations per hour				
Durability	Mechanical	15 mil. operations				
	Electrical	2.5 mil. operations				
Current and power	AC-1, Thermal current A	25	32	40		
	AC-3 200/240V kW	3.5	4.5	5.5		
	A	13	18	22		
	380/440V kW	5.5	7.5	11		
	A	12	18	22		
	500/550V kW	7.5	7.5	15		
	A	12	13	20		
	690V kW	7.5	7.5	15		
	A	9	9	18		
UL rating (50/60Hz)	Continuous current A	25	40	40		
	Single phase 110~120V HP	0.75	1	2		
	220~240V HP	2	3	3		
	200~208V HP	3	5	7.5		
	Three phase 220~240V HP	5	7.5	10		
	440~480V HP	7.5	10	15		
	550~600V HP	10	15	20		
	NEMA size	00	0	1		
Size and weight	AC control	Weight kg	0.34			
		Size(W×H×D) mm	45×73.5×86			
	DC control	Weight kg	0.51			
		Size(W×H×D) mm	45×73.5×117.7			
Auxiliary(standard)		1a1b				
Auxiliary	Side mount	UA-1				
	Front mount	AU-2, AU-4				

